

Reversible Drill and Variable Speed Reversible Drill



H6400C

- Compact, lightweight – ideal for line construction applications.
- Super Spool™ selector control for use on Open- and Closed-Center hydraulic systems.
- Rugged gear motor.
- Reversible.

SPECIFICATIONS

Capacity	
Steel	1/2" (13 mm) hole
Wood	1-1/6" (27 mm) hole
System	
Super Spool™ selector control for use on Open- and Closed-Center hydraulic systems	
Chuck	
1/2" (13 mm) key-type	
Weight	
6 lbs. (2.7 kg)	
Length	
7.5" (190 mm)	
Width	
3" (76 mm)	
Height	
9" (229 mm)	
Flow Range	
4 - 8 gpm (15 - 30 lpm)	
Operating Pressure	
1,000 - 2,000 psi (69 - 140 bar)	
Pressure Port Thd.	
9/16 - 18 SAE O-Ring	
Return Port Thd.	
3/4 - 16 SAE O-Ring	
RPM	
1,300 rpm at 6 gpm (23 lpm)	

CAT. NO.	UPC NO.	DESCRIPTION
CE H6400C	42260	Drill – 1/2" (13 mm) key-type chuck
49755	49755	Drill – 1/2" (13 mm) key-type chuck, variable speed
54923	54923	HTMA Male Coupler
54924	54924	HTMA Female Coupler

Rotary Impact Hammer Drill



- Adjustable flow control prevents overspeeding and allows precise control of drilling speed.
- Hammer drill in concrete, brick, rock, and other difficult-to-drill materials. Drill in wood or steel with auxiliary chuck.
- Super Spool™ selector control for use on Open- and Closed-Center hydraulic systems.
- Selector for drill or hammer/drill modes.
- Rugged gear motor.
- Built-in slip clutch to guard against over-torque.
- Depth gauge and auxiliary handle are removable for tight areas.
- Reversible.

SPECIFICATIONS

Capacity	
Steel	1/2" (13 mm) hole;
Wood	1-1/16" (27 mm) hole;
Concrete	3/4" (19 mm) hole, core bits 3" (76 mm)
System	
Super Spool™ selector control	
Chuck	
SDS Plus bit shanks	
Weight	
8.5 lbs. (3.9 kg)	
Length	
12" (305 mm)	
Width	
3.5" (89 mm)	
Height	
9.75" (248 mm)	
Flow Range	
5 - 10 gpm (19 - 38 lpm)	
Operating Pressure	
1,000 - 2,000 psi (69 - 140 bar)	
Pressure Port Thd.	
3/4 - 16 SAE O-Ring	
Return Port Thd.	
3/4 - 16 SAE O-Ring	
RPM	
775 - 1,100 rpm at 6.5 gpm (25 lpm)	
Blows Per Minute	
3,400 - 4,800 rpm at 6.5 gpm (25 lpm)	

CAT. NO.	UPC NO.	DESCRIPTION
CE HID6506	42309	Rotary Impact Hammer and Drill – percussion drilling SDS drill quick-change chuck
54923	54923	HTMA Male Coupler
54925	54925	HTMA Female Coupler