

## Impact Wrenches – 3/4" Square Drive and 5/8" Hex



H6510A

- Added power and torque for heavy-duty jobs.
- Twin hammer design.
- Can be used on either Open-Center or Closed-Center system.
- Adjustable torque control.
- Auxiliary handle.
- 3/4" square drive or 5/8" quick change chuck.
- Needle bearing, rugged gear motor design for long life.

CAT. NO.	UPC NO.	DESCRIPTION
CE H6510A	42268	3/4" Impact Wrench – 3/4" Square Drive
CE H6510A2	42270	3/4" Impact Wrench – 5/8" hex quick-change chuck
54923	54923	HTMA Male Coupler
54925	54925	HTMA Female Coupler

SPECIFICATIONS	
<b>Capacity</b>	3/4" square or 5/8" quick-change chuck
<b>System</b>	Open-Center/Closed-Center
<b>Weight</b>	12.3 lbs. (5.6 kg)
<b>Length</b>	9.69" (246 mm)
<b>Width</b>	3.75" (95 mm)
<b>Height</b>	11.69" (297 mm)
<b>Flow Range</b>	4 - 12 gpm (15 - 45 lpm)
<b>Operating Pressure</b>	1,000 - 2,000 psi (69 - 140 bar)
<b>Torque</b>	1,060 ft.-lb. (1,437 Nm) at 6 gpm (23 lpm)
<b>Pressure Port Thd.</b>	3/4 - 16 SAE O-Ring
<b>Return Port Thd.</b>	3/4 - 16 SAE O-Ring
<b>RPM Range</b>	2,700 rpm at 6 gpm (23 lpm) (no load)

## Impact Wrench – 1" Square Drive



CAT. NO.	UPC NO.	DESCRIPTION
CE H6520C3	42275	Impact Wrench – 1" square drive, Open-Center
54923	54923	HTMA Male Coupler
54924	54924	HTMA Female Coupler

- Heavy-duty uses in several market applications.
- Standard 1" square drive.
- Reversible.
- Hand guard.
- Auxiliary handle. (Part # F23459)
- Rugged gear motor.
- High performance twin hammer impact mechanism.

SPECIFICATIONS	
<b>Capacity</b>	1" standard square drive
<b>System</b>	Open-Center
<b>Weight</b>	19.5 lbs. (8.8 kg)
<b>Length</b>	10.75" (273 mm)
<b>Width</b>	5" (127 mm)
<b>Height</b>	12.5" (318 mm)
<b>Flow Range</b>	4 - 6 gpm (15 - 23 lpm)
<b>Operating Pressure</b>	1,000 - 2,000 psi (69 - 140 bar)
<b>Torque</b>	2,150 ft.-lb. (2,915 Nm) at 6 gpm (23 lpm)
<b>Pressure Port Thd.</b>	9/16 - 18 SAE O-Ring
<b>Return Port Thd.</b>	3/4 - 16 SAE O-Ring
<b>RPM Range</b>	2,200 rpm at 5 gpm (19 lpm) (no load)